

2Way power Divider Series							
Product NO.	Frequency(MHz)	way	Insertion loss(dB) Excluding theoretical loss	VSWR	Isolation(dB)	Power	Connector
TWPD-2N-1-30M	1-30	2	≤0.6	Typ.1.15	Typ.26dB	1W	N-F
TWPD-2S-1-30M	1-30	2	≤0.5	Typ.1.22	Typ.30dB	1W	SMA-F
TWPD-2S-1-300M	1-300	2	≤0.6	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S-1-500M	1-500	2	≤0.6	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2N-1-1000M	1-1000	2	≤1.2	Typ.1.15	Typ.26dB	1W	N-F
TWPD-2S-1-1000M	1-1000	2	≤1	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S-4-30M	4-30	2	≤0.3	Typ.1.22	Typ.30dB	1W	SMA-F
TWPD-2S-5-100M	5-100	2	≤0.4	Typ.1.22	Typ.30dB	1W	SMA-F
TWPD-2S-5-500M	5-500	2	≤0.6	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S-1-1000M	1-1000	2	≤1	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S-10-100M	10-100	2	≤0.6	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S-10-300M	10-300	2	≤0.5	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S-10-1000M	10-1000	2	≤1	Typ.1.22	Typ.30dB	1W	SMA-F
TWPD-2S-20-3000M	20-3000	2	≤7.2	Typ.1.16	Typ.24dB	20W	SMA-F
TWPD-2S-20-6000M	20-6000	2	≤4.5	Typ.1.5	Typ.18dB	20W	SMA-F
TWPD-2S-40-88M	40-88	2	≤0.45	Typ.1.25	Typ.26dB	30W	SMA-F
TWPD-2S-30-110M	30-110	2	≤1.4	Typ.1.22	Typ.28dB	1W	SMA-F
TWPD-2S-30-110M	30-110	2	≤0.8	Typ.1.16	Typ.26dB	30W	SMA-F
TWPD-2N-30-410M	30-410	2	≤1.0	Typ.1.25	Typ.20dB	200W	N-F
TWPD-2S-30-1000M	30-1000	2	≤1	Typ.1.22	Typ.30dB	1W	SMA-F
TWPD-2N-30-1000M	30-1000	2	≤2.8	Typ.1.16	Typ.26dB	20W	N-F
TWPD-2S-30-1000M	30-1000	2	≤2.5	Typ.1.16	Typ.26dB	20W	SMA-F
TWPD-2S-30-2000M	30-2000	2	≤4	Typ.1.2	Typ.26dB	20W	SMA-F
TWPD-2S-30-3000M	30-3000	2	≤2	Typ.2	Typ.9dB	1W	SMA-F
TWPD-2S-30-3000M	30-3000	2	≤4	Typ.1.25	Typ.18dB	20W	SMA-F
TWPD-2S-30-8000M	30-8000	2	≤2.8	Typ.1.25	Typ.20dB	20W	SMA-F
TWPD-2S-50-150M	50-150	2	≤0.5	Typ.1.16	Typ.30dB	1W	SMA-F
TWPD-2S-50-150M	50-150	2	≤0.6	Typ.1.3	Typ.26dB	20W	SMA-F
TWPD-2N-50-500M	50-500	2	≤1	Typ.1.15	Typ.26dB	1W	N-F
TWPD-2S-50-500M	50-500	2	≤1	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S-50-1800M	50-1800	2	≤2	Typ.1.16	Typ.26dB	20W	SMA-F
TWPD-2S-50-3000M	50-3000	2	≤4	Typ.1.25	Typ.18dB	20W	SMA-F
TWPD-2S-80-1000M	80-1000	2	≤1	Typ.1.22	Typ.30dB	1W	SMA-F
TWPD-2N80-100-1000M	100-1000	2	≤1	Typ.1.18	Typ.20dB	80W	N-F
TWPD-2N100-100-1000M	100-1000	2	≤0.8	Typ.1.18	Typ.20dB	100W	N-F
TWPD-2S1-100-1000M	100-1000	2	≤1	Typ.1.15	Typ.26dB	1W	SMA-F
TWPD-2S30-100-1000M	100-1000	2	≤1	Typ.1.25	Typ.26dB	30W	SMA-F
TWPD-2N30-100-2000M	100-2000	2	≤1.8	Typ.1.25	Typ.26dB	30W	N-F
TWPD-2N50-100-2000M	100-2000	2	≤2.8	Typ.1.25	Typ.26dB	50W	N-F
TWPD-2S20-100-2000M	100-2000	2	≤1.7	Typ.1.16	Typ.20dB	20W	SMA-F

TWPD-2S30-100-3000M	100-3000	2	≤2.5	Typ.1.16	Typ.18dB	30W	SMA-F
TWPD-2S30-100-4000M	100-4000	2	≤2	Typ.1.18	Typ.26dB	30W	SMA-F
TWPD-2S30-200-800M	200-800	2	≤0.9	Typ.1.18	Typ.28dB	30W	SMA-F
TWPD-2N30-200-1000M	200-1000	2	≤0.6	Typ.1.16	Typ.28dB	30W	N-F
TWPD-2S30-200-2000M	200-2000	2	≤1	Typ.1.15	Typ.28dB	30W	SMA-F
TWPD-2S30-200-3000M	200-3000	2	≤1.4	Typ.1.16	Typ.28dB	30W	SMA-F
TWPD-2S20-300-3000M	200-3000	2	≤0.8	Typ.1.15	Typ.28dB	20W	SMA-F
TWPD-2S30-300-6000M	300-6000	2	≤1.4	Typ.1.15	Typ.26dB	30W	SMA-F
TWPD-2S20-400-8000M	400-8000	2	≤1.4	Typ.1.15	Typ.26dB	20W	SMA-F
TWPD-2N300-500-3000M	500-3000	2	≤1	Typ.1.18	Typ.26dB	300W	N-F
TWPDE-2N30-500-6000M	500-6000	2	≤1.2	Typ.1.16	Typ.26dB	30W	N-F
TWPDE-2S30-500-6000M	500-6000	2	≤1.0	Typ.1.2	Typ.20dB	30W	SMA-F
TWPDE-2N30-500-6000M	500-6000	2	≤1.0	Typ.1.2	Typ.28dB	30W	N-F
TWPD-2S20-500-7500M	500-7500	2	≤1.2	Typ.1.16	Typ.25dB	20W	SMA-F
TWPD-2N30-500-8000M	500-8000	2	≤1.8	Typ.1.16	Typ.25dB	30W	N-F
TWPD-2S30-500-8000M	500-8000	2	≤1.5	Typ.1.16	Typ.25dB	30W	SMA-F
TWPD-2S20-500-8500M	500-8500	2	≤1.5	Typ.1.16	Typ.26dB	20W	SMA-F
TWPD-2S20-500-9000M	500-9000	2	≤1.3	Typ.1.16	Typ.26dB	20W	SMA-F
TWPD-2S20-0.5-10G	500-10000	2	≤1.8	Typ.1.16	Typ.26dB	20W	SMA-F
TWPD-2N30-0.5-18G	500-18000	2	≤1.4	Typ.1.16	Typ.18dB	30W	N-F
TWPD-2S30-0.5-18G	500-18000	2	≤1.0	Typ.1.26	Typ.24dB	30W	SMA-F
TWPD-2S-0.5-26.5G	500-26500	2	≤2.4	Typ.1.28	Typ.26dB	20W	SMA-F
TWPD-2/2.92-0.5-28G	500-28000	2	≤2.8	Typ.1.28	Typ.26dB	20W	2.92-F
TWPD-2S-0.6-12G	600-12000	2	≤1	Typ.1.26	Typ.24dB	20W	SMA-F
TWPD-2S-1-26.5G	1000-26500	2	≤1.5	Typ.1.16	Typ.22dB	20W	SMA-F
TWPD-2/2.92-1-26.5G	1000-26500	2	≤1	Typ.1.16	Typ.22dB	20W	2.92-F
TWPD-2/2.92-1-40G	1000-40000	2	≤1.8	Typ.1.16	Typ.22dB	20W	2.92-F
TWPD-2/2.92-2-26.5G	2000-26500	2	≤1.2	Typ.1.16	Typ.22dB	20W	2.92-F
TWPD-2S-3-26.5G	3000-26500	2	≤1.2	Typ.1.16	Typ.22dB	20W	SMA-F
TWPD-2S-4-14G	4000-14000	2	≤1	Typ.1.18	Typ.25dB	20W	SMA-F
TWPD-2/2.92-4-32G	4000-32000	2	≤1.4	Typ.1.16	Typ.22dB	20W	2.92-F
TWPD-2/2.92-4-40G	4000-40000	2	≤1.5	Typ.1.16	Typ.22dB	20W	2.92-F
TWPD-2S-6-26.5G	6000-26500	2	≤0.6	Typ.1.28	Typ.22dB	20W	SMA-F
TWPD-2S-7-12.4G	7000-12400	2	≤0.5	Typ.1.18	Typ.26dB	10W	SMA-F
TWPD-2S-10-20G	10000-20000	2	≤1.2	Typ.1.18	Typ.25dB	20W	SMA-F
TWPD-2/2.92-10-30G	10000-30000	2	≤0.8	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.92-10-40G	10000-40000	2	≤1	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2S-13.5-15G	13500-15000	2	≤0.5	Typ.1.18	Typ.26dB	20W	SMA-F
TWPD-2/2.92-14.5-31G	14500-31000	2	≤1	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.92-16-32G	16000-32000	2	≤1	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2S-17.6-21.2G	17600-21200	2	≤0.6	Typ.1.28	Typ.22dB	10W	SMA-F
TWPD-2S-17-22G	17000-22000	2	≤0.6	Typ.1.38	Typ.24dB	20W	SMA-F
TWPD-2/2.92-17-31G	17000-31000	2	≤1	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2S-18-24G	18000-24000	2	≤0.8	Typ.1.28	Typ.24dB	20W	SMA-F
TWPD-2S-18-26.5G	18000-26500	2	≤0.6	Typ.1.28	Typ.22dB	20W	SMA-F

TWPD-2/2.92-18-31G	18000-31000	2	≤0.8	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.92-24-30G	24000-30000	2	≤0.8	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.92-18-40G	18000-40000	2	≤1	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.4-18-50G	18000-50000	2	≤1.9	Typ.1.28	Typ.22dB	20W	2.4-F
TWPD-2/SMP-19.5-20.5 G	19500-20500	2	≤0.8	Typ.1.28	Typ.22dB	10W	SMP-M
TWPD-2/2.92-19-33G	19000-33000	2	≤0.8	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.4-18-50G	18000-50000	2	≤1.9	Typ.1.28	Typ.22dB	20W	2.4-F
TWPD-2/2.4-20-50G	20000-50000	2	≤1.5	Typ.1.3	Typ.22dB	20W	2.4-F
TWPD-2S-20-21G	20000-21000	2	≤0.8	Typ.1.18	Typ.25dB	20W	SMA-F
TWPD-2/2.4-20-30G	20000-30000	2	≤0.5	Typ.1.28	Typ.22dB	20W	2.4-F
TWPD-2/2.92-20-30G	20000-40000	2	≤1	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2S-21-26G	21000-26000	2	≤0.6	Typ.1.26	Typ.22dB	20W	SMA-F
TWPD-2/2.92-22-28G	22000-28000	2	≤0.6	Typ.1.26	Typ.22dB	20W	2.92-F
TWPD-2/2.92-24-40G	24000-40000	2	≤1	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.92-26.5-40G	26500-40000	2	≤1	Typ.1.28	Typ.24dB	20W	2.92-F
TWPD-2/2.92-26.5-40G	26000-28000	2	≤0.6	Typ.1.26	Typ.22dB	20W	2.92-F
TWPD-2/2.92-28-30G	28000-30000	2	≤0.6	Typ.1.26	Typ.22dB	20W	2.92-F
TWPD-2/2.92-26-30G	26000-30000	2	≤1.2	Typ.1.28	Typ.22dB	20W	2.92-F
TWPD-2/2.92-27-32G	27000-32000	2	≤0.6	Typ.1.38	Typ.24dB	20W	2.92-F
TWPD-2/2.92-32-40G	27000-32000	2	≤0.6	Typ.1.38	Typ.24dB	20W	2.92-F
TWPD-2/2.4-36-50G	36000-50000	2	≤1.6	Typ.1.5	Typ.14dB	15W	2.4-F
TWPD-2/2.4-43-46G	43000-46000	2	≤1.6	Typ.1.28	Typ.22dB	20W	2.4-F
More products pls contact us,OEM&ODM Service Support							